

> PRINT > COPY > SCAN > FAX

TASKalfa 6053ci

COLOUR MULTIFUNCTIONAL FOR A4/A3 (SRA3) FORMAT

HIGH-LEVEL SECURITY AS PRIORITY



Possessing all of the latest developments in technology to provide maximum security for your data, the new TASKalfa 6053ci ensures that information is kept under virtual lock and key. The deployment of innovative security features ensure that information which passes through this multifunctional product is not put at risk. Beyond protecting information, the device also offers high quality printing with vibrant colour, which can be finished with a range of flexible options, ideal for a variety of document types, lengths and formats. An award-winning engine also offers unbeatable reliability and consistency to make the product truly unique in providing a solution to the needs of a business in any industry and of any size.

- > Up to 60/55 pages per minute A4 in b/w and colour
- > Outstanding image quality due to advanced colour technology
- > User friendly and intuitive 10.1 inch operation panel
- > Advanced paper handling from A6 up to SRA3 for
- up to 7,150 sheets
- > Great range of high speed colour scanners and productive finishing options
- High-level build in security features including data encryption, Trusted
 Platform Module, Secure Boot and Run Time Integrity Check
- > Long-life components providing exceptional efficiency and reliability, and less waste
- > Optional Fiery Controller for highest productivity and colour quality





In today's landscape, securing your printing environment is a competitive advantage for your organisation. The new TASKalfa 6053ci runs sophisticated security features to protect your business data from costly data breaches.

GENERAL

Technology: KYOCERA TASKalfa Laser Colour, HyPAS

Technology: No constraints solution platform Touch panel size: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel

Engine speed (pages per minute): Up to 55/27 ppm A4/A3 in colour, up to 60/30 ppm A4/A3 in b/w; Duplex print speed: 60 ppm A4; Duplex copy speed: 60 ppm, A4 Resolution: 4800dpi equivalent x 1200dpi (print), 600 x 600 dpi (cara (copu)) 600 dpi (scan/copy)

Warm-up time from power on: Approx, 17 seconds or less Time to first print: 3.8 / 5.1 seconds or less in b/w / colour

Time to first copy: 4.1/ 6.2 seconds or less in b/w / colour (DP); 3.4/ 4.4 seconds or less in b/w / colour (Platen)

CPU: QorlQ T1024 (Dual Core) 1.2GHz

Memory (standard max.): 4 GB RAM + 8 GB SSD +

IDD Standard interface: Standard interface: USB 3.0 (Super-(10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 2 eXUIO slots, for optional internal print server or for optional fax system, slot for optional Wireless LAN, Slot for optional SD Card, NFC tag **Dimensions (W x D x H):** Main unit: 602 x 665 x 790 mm **Weight:** Main unit: Approx. 95 kg **Power source:** AC 220 V ~ 240 V, 50/60 Hz

Power consumption: Printing: 990 W Copying: 990 W

Ready mode: 60 W

Low power mode: 50 W Sleep mode: 0.7 W

Noise (sound pressure level ISO 7779 measurement distance of 1 meter): Copying/Printing: 54.6 dB (A) in colour

Stand-by: 35 dB (A)

Safety standards: GS, TÜV, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: Multipurpose tray: 150 sheets, 52–300 g/m² (Banner 136–163 g/m²), A6R–SRA3 (320 x 450 mm), Custom (98 x 148 to 297 x 4572 mm), Banner max. 304.8 x 1,220 mm; Standard universal paper cassette: 2 x 500 sheets, 52 – 300 g/m², Upper cassette A6R up to A4R, lower

Cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4 **Duplex unit:** Duplex as standard supports

A6R – SRA3, 64 – 256 g/m² **Output capacity:** Standard 500 sheets face-down, max. output capacity 4,300 sheets

PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS

Operating systems: All current Windows operating systems, Mac OS X Version 10.9 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPV3, quick copy, proof and hold, private print, job storage functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

COPY FUNCTIONS

Max. original size: A3 / Ledger Continuous copying: 1–9999 Zoom range: 25–400% in 1% steps Preset magnification ratios: 5R/5E, Exposure mode: Auto, manual: 16 steps Image adjustments: Text + photo, text, photo, Diagram/map

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, skip blank page, ID copy

SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB, Scan to USB Host, Scan to box, Network TWAIN, WIA/WSD

Scan speed: 220 images per minute (300 dpi, A4 duplex, with DP-7130) in b/w and colour Scan resolution; 600dpi x 600dpi , 400dpi x 400dpi , 200dpi x 400dpi, 300dpi x 300dpi , 200dpi x 200dpi , 200dpi x 100dpi; 256 greyscales per colour

Max. scan size: A3, Ledger **Original recognition:** Text, photo, text + photo, Light Text / Fine Line, optimised for OCR

File types: TIF, PDF, PDF, AJ, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF(option), MS Office file(option)

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Compatibility: 110-1 Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Max. 3 seconds (JBIG) Scanning speed: 2.0 seconds or less Maximum original size: A3, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH Features: Network faxing, rotate transmission, rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmis-

sion and reception, broadcast, Optional Internet-fax, dual fax with second fax system 12

CONSUMABLES

Average continuous toner yield in accordance with 5% coverage A4.

TK-519K Toner-Kit: Toner black for 30,000 pages A4 TK-8519C, TK-8519M, TK-8519Y Toner-Kits: Toner cyan, magenta, yellow for 20,000 pages

WT-8500 Waste Toner Bottle: 40,000 sheets (in accord-ance with 5% coverage b/w : colour = 7 : 3) Staple cartridge:

SH-10 5000 x 3 staples, for DF-7100, DF-7120 and BF-730 SH-12 5000 x 3 staples, for DF-7110 SH-14 5000 x 5 staples, for DF-7130

Fax System 12

Internet Fax Kit (A)

Scan Extension Kit (A): Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office (docx, xlsx, pptx) Printing System 15: Fiery Controller

Printing System Interface Kit 15: Interface board for Fiery Paper handling DP-7100 Document processor: (Reversing), 140 sheets,





Phone: 08 9328 4600 Email: dds@multifaxdds.com.au Web: www.multifaxdds.com.au

YOUR KYOCERA BUSINESS PARTNER

KYOCERA Document Solutions New Zealand is the trading name of the New Zealand branch of KYOCERA Document Solutions Australia Pty Ltd a corporation incorporated in Australia

KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their resp holders and are hereby acknowledged.



Document Solutions

35-160 g/m² (simplex), 50-120 g/m² (duplex), A6R-A3, Banner up to 1,900 mm DP-7110 Document processor: (one-path duplex scanning)

270 sheets at 50 - 80 g/m², 35 - 220 g/m² (simplex), 50 - 220 g/m² (duplex), A6R - A3, Banner up to 1,900 mm **DP-7130 Document processor:** (one-path duplex scanning with ultrasonic sensor), 270 sheets at 50 - 80 g/m², 35–220 g/m² (simplex), 50–220 g/m² (duplex), A6R–A3, Banner up to 1,900 mm

DT-730(B) Document trav

PF-7100 Paper feeder: 2x 500 sheets, 52-300 g/m², AGR – SRA3 **PF-7110 Paper feeder:** 2x 1,500 sheets, 52 – 300 g/m², A4,

DF-7120 A4 side Deck: 3,000 sheets, 60–300 g/m², A4, B5 **DF-7100 Inner finisher:** 500 sheets A4, 52–300 g/m², A6P_SPA3

A6R-SRA3 DF-7110' Document finisher + AK-7110: Main tray: 4,000 sheets A4; Sub tray: 200 sheets A4; 52 - 300 g/m²; A6R - SRA3 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions DF-7120' Document finisher + AK-7110: 1,000 sheets A4, 52 - 300 g/m², A6R - SRA3, Stapling up to 50 sheets A4 or 30 sheets A3 at 3 position DF-7130' Document finisher + AK-7110: Main tray: 4,000 sheats A4', Sub tray: -00 sheats S-300 g/m² A6R-SRA3

Stapling up to 100 sheets A4 or 50 sheets A3 at 3 positions sheets A4: Sub tray: 200 sheets 52-300 g/m² A6R-SRA3:

AK-7110 Attachment kit for DF-7110, DF-7120 and DF-7130, 100 sheets, 52–300 g/m², A6R–SRA3, * Bridge unit AK-7110 is required when using a finisher PH-7C Punch unit for DF-7110/DF-7120/ DF-7130: 2-hole/4-

hole, 60 - 256 g/m², A5R - A3 MT-730(B) Mailbox sorter for DF-7110:

Tor DF-7110: 7 bins x 100 sheets A4, 50 sheets A3/B4, 60-163 g/m² BF-730 Booklet and tri-folding unit for DF-7110 Half-folding: 52-256 g/m², A3, B4, A4R Booklet: Max. 16 sheets (64 pages, 60-90 g/m²) Non-strel folding. May G sheet (60 000 g/m²)

Non-staple folding: Max. 5 sheets (60–90 g/m²) Tri-folding: Max. 5 sheets (60–105 g/m², A4R) Multi tri-folding: 5 sheets (60–90 g/m²), 3 sheets $(91-105 g/m^2)$

BF-9100 Booklet and tri-folding unit for DF-7130 Half-folding: 52–256 g/m², A3, B4, A4R Booklet : Max 20 sheets (80 pages, 60-90g/m²) or Max 13

Sheets (52 pages 91-105g/m²) Non-staple : Max 5 sheets(60-90g/m²) or Max 3 sheets(91-105g/m²)

Tri-folding : Max 5 sheets(60-90g/m²) or Max 3 sheets(91-JS-7100 Job separator:

PH-7120: Inner punch unit for DF-7100 inner finisher PH-7130: Inner punch unit for DF-7100 inner finisher

Swedish type Banner Guide 10: Banner paper feeding guide, 10 sheets Keybordholder 10

NK-7120 Numeric keypad USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available. The

card holder is standard

UG-33 AC: ThinPrint support UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/ Diablo 630)

Optional interface IB-35: Direct Wi-Fi Interface

IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/

1 000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)

Platen cover (E) 1290: Cabinet for two drawer configuration





