

> PRINT > COPY > SCAN > FAX

TASKalfa 5003i

MONOCHROME MULTIFUNCTIONAL FOR FOR A4/A3 FORMAT

SAFEGUARD YOUR SENSITIVE INFORMATION



Leading the way in secure printing, copying and scanning, the new TASKalfa 5003i ensures that information is kept under virtual lock and key. By enabling professionals to operate without compromising on the security of their documentation, this TASKalfa device provides a highly secure solution to office document needs. This multifunctional product also offers high quality monochrome printing which can be finished with a range of flexible options to provide a rounded offer for companies of all sizes. An award-winning engine also provides unbeatable reliability and consistency to strengthen its offering as the complete solution to office document requirements.

- > Up to 50/25 pages A4/A3 per minute
- > User friendly and intuitive 10.1 inch operation panel
- > Flexible paper-handling from A6 up to SRA3 for up to 7,150 sheets
- > Great range of high speed colour scanners and productive finishing options
- > High-level build in security features including data encryption, Trusted Platform Module, Secure Boot and Run Time Integrity Check
- \gt Increase productivity and save time with the Human Detection Sensor
- > Comprehensive support for all state-of-the-art mobile communications
- Long-life components providing exceptional efficiency and reliability, and less waste



TASKalfa Printing environments can serve as an entry point for hackers to hijack sensitive information. The new TASKalfa 5003i enhances security to adapt to the new de mands of today's digital businesses.

Technology: KYOCERA TASKalfa Laser Monochrome,

HyPAS solution platform

Touch panel size: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel mounted

Engine speed (pages per minute): Up to 50/25 ppm A4/ A3; Duplex print speed: 50 page per minute, A4; Duplex copy speed: 50 pages per minute, A4 **Resolution:** 4800dpi equivalent x 1200dpi (print), 600 x

600 dpi (scan/copy)

Warm-up time from power on: Approx. 17 seconds or less Time to first print: 4.3 seconds or less Time to first copy: 4.5 seconds or less (DP); 3.7 seconds or less (Platen) CPU: QorlQ T1024 (Dual Core) 1.2GHz

Memory (standard max.): 4 GB RAM + 8 GB SSD + 320 GB HDD

Standard interface: Standard interface: USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), optional Wi-Fi (IEEE 802.1b/g/n), 2 eKUIO slots, for optional internal print server or for endur stots, for optional internal print server or for optional fax system, slot for optional Wireless LAN, Slot for optional SD Card, NFC tag

Dimensions (W x D x H): Main unit: 602 x 665 x 790 mm

Weight: Main unit: Approx. 83 kg

Power source: AC 220 V ~ 240 V, 50/60 Hz

Power consumption:

Printing: ACO W

Printing: 740 W Copying: 740 W Ready mode: 50 W

Low power mode: 50 W

Sleep mode: 0.7 W
Noise (sound pressure level ISO 7779 measurement distance of 1 meter):

Copying/Printing: 53.1 dB (A) Stand-by: 35 dB (A) Safety standards: GS, TÜV, CE.

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 150-sheet multipurpose tray, 52 – 300 g/m² (Banner 136 – 163 g/m²), A6R – SRA3 (320 x 450 mm), Custom (98 x 148 to 297 x 457.2 mm), Banner max. 304.8 x 1,220 mm; 2x 500-sheet universal paper cassette, 52 – 300 g/m², Upper cassette A6R up to A4R, lower cassette A6R up to SRA3,

Max, input capacity with options: 7.150 sheets A4

Duplex unit: Duplex as standard supports

A6R-SRA3, 64-256 g/m²

Output capacity: Standard 500 sheets face-down, max. output capacity 4,300 sheets

PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and

Operating systems: All current Windows operating systems, Mac OS X Version 10.9 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec,SNMPy3, quick copy, proof and hold, private print, iob storage functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

Max. original size: A3 / Ledger Continuous copying: 1-9999 Zoom range: 25-400% in 1% steps

Preset magnification ratios: SR/SE, Digital features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, Skip blank page, ID copy **Exposure mode:** Auto, manual: 16 steps

Image adjustments: Text + photo, text, photo,

SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB Scan to USB Host, Scan to box, Network TWAIN, WIA/WSD

Scan speed: 220 ipm (300 dpi, A4 duplex, with DP-7130) in b/w and colour

Scan resolution: A4 - 600dpi x 600dpi , 400dpi x 400dpi , 200dpi x 400dpi , 300dpi x 300dpi , 200dpi x 200dpi , 200dpi x 100dpi ; 256 greyscales per colour

Max. scan size: A3, Ledger
Original recognition: Text, photo, text + photo, Light Text
/ Fine Line, optimised for OCR

File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF(Option), MS Office file(Option)

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Max. 3 seconds (JBIG)

Scanning speed: 2.0 seconds or less
Address book: 2000 entries
Maximum original size: A3, Banner up to 1,600 mm

Compression method: JBIG, MMR, MR, MH Features: Network faxing, rotate transmission, rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broad-cast, Optional Internet-fax, dual fax with second fax

system 12

CONSUMABLES

Average continuous toner yield in accordance with 6%

TK-6329 Toner-Kit: Toner black for 30,000 pages A4 WT-8500 Waste Toner Bottle: 40,000 sheets (in accordance with 6% coverage b/w: colour = 7:3) **Staple cartridge:**

SH-10 5000 x 3 staples, for DF-7100, DF-7120 and BF-730 SH-12 5000 x 3 staples, for DF-7110 SH-14 5000 x 5 staples, for DF-7130

OPTIONS

Fax System 12 Internet Fax Kit (A) Scan Extension Kit (A): Scan to searchable PDF solution (embedded OCR),

convert to PDF or MS Office (docx, xlsx, pptx)

Paper handling

DP-7100 Document processor: (Reversing), 140 sheets, 35–160 g/m² (simplex), 50–120 g/m² (duplex), A6R – A3 Banner up to 1,900 mm

DP-7110 Document processor: (one-path duplex scanning) 270 sheets at $50 - 80 \text{ g/m}^2$, $35 - 220 \text{ g/m}^2$ (simplex), $50 - 220 \text{ g/m}^2$ (duplex), A6R - A3 Banner up to

DP-7130 Document processor: (one-path duplex scanning with ultrasonic sensor), 270 sheets at 50 - 80 g/m², 35–220 g/m² (simplex), 50–220 g/m² (duplex), A6R–A3, Banner up to 1,900 mm DT-730(B) Document tray

PF-7100 Paper feeder: 2x 500 sheets, 52 – 300 g/m², A6R – SRA3

PF-7110 Paper feeder: 2x 1,500 sheets, 52 - 300 g/m², A4,

PF-7120 A4 side Deck: 3,000 sheets, 60 – 300 g/m², A4, B5 **DF-7100 Inner finisher:** Main tray: 500 sheets A4, 52–300 g/m², A6R-SRA3

DF-7110* Document finisher + AK-7110:

Main tray: Max. 4,000 sheets A4; max. 52-300 g/m²; max. A6R – SRA3

Sub tray: 200 sheets A4; 52–300 g/m²; A6R – SRA3 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions,

DF-7120' Document finisher + AK-7110: Main tray: 1,000 sheets A4, 52–300 g/m², A6R – SRA3, Stapling up to 50 sheets A4 or 30 sheets A3 at 3 position **DF-7130* Document finisher + AK-7110:** Main tray: 4,000 sheets A4; Sub tray: 200 sheets A4

52-300 g/m² A6R-SRA3; Stapling up to 100 sheets A4 or

52–300 g/m² A6K–5KA3; Stapling up to 100 sheets A4 or 50 sheets A3 at 3 positions AK-7110 Attachment kit for DF-7110, DF-7120 and DF-7130: 100 sheets, 52–300 g/m², A6R–5RA3, * Bridge unit AK-7110 is required when using a finisher PH-7C Punch unit for DF-7110/DF-7120/ DF-7130: 2-hole/

4-hole, 60 - 256 g/m2, A5R - A3

MT-730(B) Mailbox sorter for DF-7110: 7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 1 BF-730 Booklet and tri-folding unit for DF-7110

Half-folding: 52–256 g/m², A3, B4, A4R Booklet: Max. 16 sheets (64 pages, 60–90 g/m²) Non-staple folding: Max. 5 sheets (60–90 g/m²) Tri-folding: 60–105 g/m², A4R Multi tri-folding: 5 sheets (60–90 g/m²), 3 sheets (01.106 r/m²).

BF-9100 Booklet and tri-folding unit for DF-7130

BI-910 BOOKER and tri-rotaing unit for DI-7130 Half-folding: 52-256 g/m², A3, B4, A4R Booklet: Max 20 sheets (80 pages, 60-90g/m²) or Max 13 sheets(52 pages 91-105g/m²) Non-staple: Max 5 sheets(60-90g/m²) or Max 3 sheets(91-105g/m²)

Tri folding: Max 5 sheets(60-90g/m²) or Max 3 sheets(91-

105g/m²) JS-7100 Job separator:

100-sheet internal job separator, 52 – 300 g/m², A5R – SRA3

PH-7120: Inner punch unit for DF-7100 inner finisher

Banner Guide 10: Banner paper feeding guide, 10 sheets

Keybordholder 10

NK-7120 Numeric keypad

USB IC Card Reader + Card Authentication Kit (B):
Support for various authentication keys available.

The card holder is standard

UG-33 AC: ThinPrint support
UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/

Diablo 630)

Optional interface IB-35: Direct Wi-Fi Interface

IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/

IB-51: Wireless LAN Interface (802.11b/g/n) Platen cover (E) 1290: Cabinet for two drawer configuration

















digital document solutions

Phone: 08 9328 4600

Email: dds@multifaxdds.com.au Web: www.multifaxdds.com.au KYOCERA Document Solutions New Zealand is the trading name of the New Zealand branch of KYOCERA Document Solutions Australia Pty Ltd a corporation incorporated in Australia

KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their resp holders and are hereby acknowledged.

